TA205B Handset Intercom Suite Station Specification Sheet

IL081
Section A
Rev. 8 - 05/2004



TA205B

ARCHITECTS' AND ENGINEERS' SPECIFICATION

Handset intercom suite station shall be TekTone® TA205B, or approved equal. The TA205B shall be molded of a high-impact flame retardant ABS plastic. Dynamic speech elements shall be used and a push button shall be provided for door lock release. The suite station shall be mounted on a standard single gang electrical box and have screw terminals for wiring hook-up.

FEATURES

The TA205B Handset Intercom Suite Station is designed especially for intercom use. It features compact modern styling and advanced electronic design using dynamic speech elements. The TA205B includes an integral push button for door lock release, and a reliable hook cradle switch. The TA205B is molded of a high impact flame retardant ABS plastic and is suitable for a variety of applications.

- Clear, true voice reproduction
- Integral door lock release push button
- Easy to install and use
- Audible signal tone

SPECIFICATIONS

Dimensions:	Height:	8.5" (216 mm) (not including cord)
	Width:	3.5" (89 mm)
	Depth:	3.25" (82 mm)
Construction:	High impact flame retardant ABS plastic	
Speech Elements:	Dynamic with voice response	
Push Button:	Replaceable with plated, self-wiping contacts	
Connections:	Screw terminals	
Color:	White	
Mounting:	Standard single gang electrical box, installed vertically	

REQUIRED COMPONENTS

CM193 ***or*** AM193	Entrance Panel
PK205	Amplifier
SS102A ***or*** SS105B	Transformer
PO001	Electric Door Opener (optional)

www.tektone.NET
277 Industrial Park Road • Franklin, NC 28734 • Phone (828) 524-9967 • Fax (828) 524-9968
Email: tektone@tektone.net • Technical Assistance Email: teksupt@tektone.net
TekTone®'s quality system is registered by UL® to the ISO 9001:2000 standard. (File #A10766.)