



SF301G, SF302G Call Cords Specification Sheet

IL434
Section E
Rev. 13 - 11/2005



SF301G

ARCHITECTS' AND ENGINEERS' SPECIFICATION

The call cord shall be TekTone® SF301G, SF302G or approved equal. Model SF301G shall include a single squeeze bulb for call origination. Model SF302G shall include two squeeze bulbs in a “Y” configuration to a single plug.

The call cords shall permit simple call origination and shall be acceptable for use in oxygen, geriatric or general applications.

The momentary contact, air operated switch shall be built into the plug and shall be activated by a slight pressure to the squeeze bulb. A 6' long vinyl tube shall connect the squeeze bulb to the stainless steel plug. A stainless steel bed clamp shall be permanently affixed to the call cord, but shall be adjustable along the length of the cord.

Call cords shall be UL® 1069 Listed.

FEATURES

TekTone® SF301G and SF302G Call Cords are for use with the Tek-CARE® NC110N, NC150N, NC200N and NC300II Nurse Call Systems, where 1/4" phono jacks are used. Patient stations include SF100C, IR151B, IR152B, SF380C, SF380P and SF530.

SF301G and SF302G Call Cords are specifically designed for use in geriatric and oxygen environments, but may also be used in general applications. To place a call, the patient applies slight pressure to the squeeze bulb using any part of the body. The force of air through the vinyl tubing closes a switch in the plug, thus placing a call. An adjustable bed clip is supplied for the SF301G and is attached to the call cord. Two adjustable bed clips are supplied with the SF302G.

- UL® 1069 Listed
- Sensitive touch activation
- Oxygen tent safe
- Ideal for geriatric use
- Momentary, air-activated switch
- Adjustable bed clip(s)

SPECIFICATIONS

Switch:	Momentary contact, air activated	
Plug:	Stainless steel	
Cord:	Vinyl tubing	
Electrical:	Rated current 1/3 amp, 24 VAC-VDC	
Dimensions:	Cord:	6' long (1.83 m)
	Plug:	1.25" long (32 mm)
	Bulb:	1.5" diameter (38 mm)

REQUIRED COMPONENTS

Tek-CARE®500 Wireless Emergency Call System
with SF530 Room Stations

or

Tek-CARE®NC300II Nurse Call System
with SF380C or SF380P Patient Stations

or

Tek-CARE®NC200N or NC150N Nurse Call Systems
with IR151B or IR152B Patient Stations

or

Tek-CARE®NC110N Nurse Call System
with SF100C Patient Stations

www.tektone.NET

277 Industrial Park Road • Franklin, NC 28734 • Phone (828) 524-9967 • Fax (828) 524-9968

Email: tektone@tektone.net • Technical Assistance Email: teksupt@tektone.net

TekTone®'s quality system is registered by UL® to the ISO 9001:2000 standard. (File #A10766.)