



# LI386B Addressable Dome/Zone Light Specification Sheet

IL547  
Section E  
Rev. 9 - 11/2005



**LI386B Addressable Dome/Zone Light**

## ARCHITECTS' AND ENGINEERS' SPECIFICATION

Dome/Zone light shall be TekTone® LI386B or approved equal. The supervised corridor light shall be sectional in design. Lights shall include one each amber, red and green flame-retardant translucent polycarbonate plastic lenses, and one white flame-retardant translucent polystyrene plastic lens. All lenses shall be mounted on a flame-retardant (UL® 94V-0) plastic base panel. The lenses shall be individually removable without the use of tools, for ease of bulb replacement. The four bulbs, in conjunction with the different colored lenses, shall provide for indication of patient call priority and staff presence. The Dome/Zone light shall have lamp supervision.

The stations, and the wiring from the central equipment (CE) to the stations, shall be supervised. The unit shall provide visual and digital communications to and from the CE. Connections shall be plug-in type. The LI386B shall be a stand-alone unit that connects directly to the CE.

The Dome/Zone light shall be UL® 1069 Listed.

## FEATURES

TekTone®'s LI386B Dome/Zone Light with built-in multipurpose station provides visual indication of calls originating from bath, emergency and code call stations when used as a dome light. The LI386B also indicates calls originating from patient, staff and duty stations when used as a zone light. The LI386B also indicates all calls from the zones to which those stations are assigned and provides communication to and from the central equipment, including the nurse master station and monitor. It is used with remotely-mounted devices such as switches, contact closures, or other signal-originating equipment. No controls are provided.

- UL® 1069 Listed
- Supervised
- Easy bulb replacement
- Excellent visibility
- Lamp supervision
- Interchangeable lens caps
- Simplified multiplex wiring
- Plug-in connectors

## SPECIFICATIONS

Dimensions:	Height: 4.5625" (115 mm)
	Width: 4.5625" (115 mm)
	Depth: 3.3" (84 mm)
Bulbs:	#1829 28v. 70mA
Power:	24 VDC, 51 mA
Connections:	Ramp lock plug-in type
Finish:	Base is flame retardant (UL® 94V-0) plastic. Amber, red and green lenses are flame-retardant translucent polycarbonate plastic. White lens is flame retardant translucent polystyrene plastic.
Housing:	Standard dual gang box and ring.

## REQUIRED COMPONENTS

Tek-CARE®NC300II Nurse Call System

[www.tektone.NET](http://www.tektone.NET)

277 Industrial Park Road • Franklin, NC 28734 • Phone (828) 524-9967 • Fax (828) 524-9968

Email: [tektone@tektone.net](mailto:tektone@tektone.net) • Technical Assistance Email: [teksupt@tektone.net](mailto:teksupt@tektone.net)

**TekTone®'s quality system is registered by UL® to the ISO 9001:2000 standard. (File #A10766.)**